


American Pride - 526 Crest Road - Flat Rock, NC 28731  
828-697-8847 Fax 828-697-7094

### Product Data Specifications

Woodfield Model#9614R1CA(Carolina), 9614R1CL(Classic), 9614R1HE(Heritage),  
For Surface Mounted Cabinets Replace "R" with "S" EXAMPLE: 9614S1CA

**MIRROR:** 14" x 20" Single Strength (.09375) CCE  
**OVERALL SIZE:** 17-1/2" x 23-1/2" x 4"  
**ROUGH OPENING:** 14" x 18 x 2.5" **STORAGE DEPTH:** 3.5"  
**SHELVES:** 3 Fixed white styrene  
**HINGE:** 2 Split Butt Tri-brite 2-1/2" hinges  
**DOOR OPERATION:** One Zinc Plated Riveted on Steel Clip Catch for On the Move Applications  
**MOUNTING HARDWARE:** 4 #8 x 1 1/2" Steel Tapping Screws  
**FRAME MATERIAL:** Solid Oak with a choice of 3 finishes Light to dark  
Carolina(CA), Classic(CL), Heritage(HE)  
**REVERSIBLE:** Yes  
**DOOR BACKING:** White High Impact Polystyrene .060 Thickness  
**CABINET:** Injection Molded in White  
**For Surface Mount OD: 15.5" x 19.5" x 4"**  
Typical Wall Thickness .110 Material: High Impact Polystyrene  
All Color Non-Toxic 1.5 Notched Izod (minimum)  
Specific Gravity 1.05, 73 /28 F Heat Deflection Annealed, 264 psi 185  
Vicat Softening Point, F 202 C 94  
Tensile Strength at yield (2.0 in/min) psi 3400  
Ultimate Elongation % (0.2 in/min)(5mm/min) 35  
Flexular Modulus (0.05 in/min) psi 300,000 Hardness, Rockwell M 20  
Izod Impact, 1/4" - 8.4 mm @ 78 F/23 C 1.4 ft.-lb. 75 J/m

### 96 (Standard, 1C or 1D) Plastic(Polystyrene) Recessed or Surface Mounted Cabinet



Storage Depth(3.5")  
Covers up 15.5" x 19.5"  
3 Fixed Shelves  
R.O.(14" x 18"x 2.5")